

Document No. **UK PA5600 210806 001 ISS 01**

Manufacturer **Weidmüller Interface GmbH & Co. KG**

Address **Klingenbergstr. 26
32758 Detmold, Germany**

Object of the declaration **TERMOPTO solid-state relays**

☒ Continued on page 2

The manufacturer attests, in sole-responsibility, that the object of the declaration described above is in conformity with the essential requirements of directive(s):

		Directive	
☒	The Electrical Equipment (Safety) Regulations 2016	SI 2016/1101	SI2019/696(Schedule23) SI 2020/1460
☒	The Electromagnetic Compatibility Regulations 2016	SI 2016/1091	SI2019/696(Schedule20) SI 2020/1460
☐	The supply of Machinery (Safety) Regulations 2008	SI 2008/1597	SI2019/696(Schedule12) SI 2020/1460
☐	The Radio Equipment Regulations 2017	SI 2017/1206	SI2019/696(Schedule29) SI 2020/1460
☒	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 RoHS	SI 2012/3032	SI2019/188
☐	The Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres Regulations 2016 Marking (Equipment Group, Category, Atmosphere)	SI 2016/1107	SI2019/696Schedule25) SI 2020/1460

Document No.

UK PA5600 210806 001 ISS 01

References to the relevant EN or BSEN designated standards used, or references to the specifications, in relation to which conformity is declared:

EMV / EMC:
EN 61326-1:2013

ROHS:
EN IEC 63000:2018

References to the relevant EN or BSEN designated not harmonised standards used, or references to the specifications, in relation to which conformity is declared:

NSR / LVD
EN 50178:1997

Object of the declaration (continued from page 1)

Typ	Order No.	Typ	Order No.	Typ	Order No.
TOS 120VAC/48VDC 0.5A RC	1180290000	TOP 24VAC/48VDC 0,1A	8950860000	TOP 120VAC/48VDC 0,5A	8951080000
TOP 120VAC/48VDC 0.5A RC	1188830000	TOP 48-60VAC/48VDC 0,1A	8950870000	TOP 230VAC/48VDC 0,5A	8951090000
TOP 230VAC/48VDC 0.5A RC	1189260000	TOP 120VAC/48VDC 0,1A	8950880000	TOS 5VDC/230VAC 0,1A	8951100000
TOS 230VAC/48VDC 0.5A RC	1189270000	TOP 230VAC/48VDC 0,1A	8950890000	TOS 12VDC/230VAC 0,1A	8951110000
TOP 24VDC/24VDC 4A	1254880000	TOS 5VDC/48VDC 0,5A	8950900000	TOS 24VDC/230VAC 0,1A	8951120000
TOS 24VDC/24VDC 4A	1275100000	TOS 12VDC/48VDC 0,5A	8950910000	TOS 48-60VDC/230VAC 0,1A	8951130000
TOS 5VDC/48VDC 0,1A	8950700000	TOS 24VDC/48VDC 0,5A	8950920000	TOS 110VDC/230VAC 0,1A	8951140000
TOS 12VDC/48VDC 0,1A	8950710000	TOS 48-60VDC/48VDC 0,5A	8950930000	TOS 220VDC/230VAC 0,1A	8951150000
TOS 24VDC/48VDC 0,1A	8950720000	TOS 110VDC/48VDC 0,5A	8950940000	TOP 5VDC/230VAC 0,1A	8951160000
TOS 48-60VDC/48VDC 0,1A	8950730000	TOS 220VDC/48VDC 0,5A	8950950000	TOP 12VDC/230VAC 0,1A	8951170000
TOS 110VDC/48VDC 0,1A	8950740000	TOP 5VDC/48VDC 0,5A	8950960000	TOP 24VDC/230VAC 0,1A	8951180000
TOS 220VDC/48VDC 0,1A	8950750000	TOP 12VDC/48VDC 0,5A	8950970000	TOP 48-60VDC/230VAC 0,1A	8951190000
TOP 5VDC/48VDC 0,1A	8950760000	TOP 24VDC/48VDC 0,5A	8950980000	TOP 110VDC/230VAC 0,1A	8951200000
TOP 12VDC/48VDC 0,1A	8950770000	TOP 48-60VDC/48VDC 0,5A	8950990000	TOP 220VDC/230VAC 0,1A	8951210000
TOP 24VDC/48VDC 0,1A	8950780000	TOP 110VDC/48VDC 0,5A	8951000000	TOS 24VAC/230VAC 0,1A	8951220000
TOP 48-60VDC/48VDC 0,1A	8950790000	TOP 220VDC/48VDC 0,5A	8951010000	TOS 48-60VAC/230VAC 0,1A	8951230000
TOP 110VDC/48VDC 0,1A	8950800000	TOS 24VAC/48VDC 0,5A	8951020000	TOS 120VAC/230VAC 0,1A	8951240000
TOP 220VDC/48VDC 0,1A	8950810000	TOS 48-60VAC/48VDC 0,5A	8951030000	TOS 230VAC/230VAC 0,1A	8951250000
TOS 24VAC/48VDC 0,1A	8950820000	TOS 120VAC/48VDC 0,5A	8951040000	TOP 24VAC/230VAC 0,1A	8951260000
TOS 48-60VAC/48VDC 0,1A	8950830000	TOS 230VAC/48VDC 0,5A	8951050000	TOP 48-60VAC/230VAC 0,1A	8951270000
TOS 120VAC/48VDC 0,1A	8950840000	TOP 24VAC/48VDC 0,5A	8951060000	TOP 120VAC/230VAC 0,1A	8951280000
TOS 230VAC/48VDC 0,1A	8950850000	TOP 48-60VAC/48VDC 0,5A	8951070000	TOP 230VAC/230VAC 0,1A	8951290000

Detmold, 03.12.2021

place, date

legally binding signature

name and function

Thomas Peter
Head of Digital Signaling & Protection

This declaration certifies compliance with the indicated directive but no warranty of properties. The safety instructions of the accompanying product documentation shall be observe.