



HOLE PATTERN

PCB-0 1,4 TILL POLE 8
PCB-0 1,5 FROM POLE 9

1/1

24	116,84	4,600
23	111,76	4,400
22	106,68	4,200
21	101,60	4,000
20	96,52	3,800
19	91,44	3,600
18	86,36	3,400
17	81,28	3,200
16	76,20	3,000
15	71,12	2,800
14	66,04	2,600
13	60,96	2,400
12	55,88	2,200
11	50,80	2,000
10	45,72	1,800
9	40,64	1,600
8	35,56	1,400
7	30,48	1,200
6	25,40	1,000
5	20,32	0,800
4	15,24	0,600
3	10,16	0,400
2	5,08	0,200
n	L1 [mm]	L1 [inch]

For the mounting of PCBs, it should be noted that the rated data relates only to the PCB components alone.

The necessary creepage and clearance paths must be observed in connection with the respective applicant in accordance to IEC 664 / VDE 0110.

The current-carrying capacity and pitch tolerance is to be determined according to DIN IEC 326 part 3 very fine.

Weidmüller PCB components are tested to the DIN EN 61984 standard, and are valid for its field of application. Provided that the components are used to the intended purpose, all requirements with respect to the occurring of electrical, mechanical, thermic and corrosive stress will be satisfied.

P=PITCH

SHOWN: SL 5.08/4/90 B

STIFTLAENGE L PIN LENGTH L	TOLERANZ TOLERANCE
3,2	0,1
	-0,3
4,5	0,1
	-0,3
	n L1 [mm] L1 [inch]

DIN ISO 2768-m
101482/5
07.02.18 HELIS_MA 00

Modification

	Date	Name
Drawn	18.10.2010	HERTEL_S
Responsible		HERTEL_S

Scale: 2:1

Checked 27.02.2018 HELIS_MA

Supersedes: .

Approved LANG_T

Weidmüller

3 48753 04
Drawing no. 02 of 05 sheets

SL 5.08HC/.../90...
STIFTLEISTE
MALE HEADER

Product file: SL-HP 5.08

7377