

Changeover to ESD bags for “Tape on Reel” products

Dear Madam or Sir,

Product adaptations serve the purpose of continuous product and/or process improvement. The listed products are delivered in a modified version. Please pass this product information on to your employees and, if needed, to your customers.

1. General Overview

Type of notification: ☒ PCN ☐ PDN ☒ Short-term action

Short-term action due to:

- | | |
|---|---|
| <input type="checkbox"/> Software / Firmware Bugfix | <input type="checkbox"/> Short term delivery stop by supplier |
| <input type="checkbox"/> Short term recall by supplier | <input type="checkbox"/> Force majeure |
| <input checked="" type="checkbox"/> Product improvement with customer benefit | <input type="checkbox"/> other |

2. Technical changes

The packaging bag of Signal SMT-headers and SMT-terminals is changed to a variant that is safe from electrostatic discharge. The new packaging bag meets the technical requirements of IEC 61340-5-1 and has a surface resistance of $10^4 \leq R_s < 10^{11}$. Visually, the new bag differs from the old bag by a pink color.



3. Availability

This notification is to inform you that the change will be implemented in production as of March 2023. There will be no stock adjustment. Therefore, if you order several packaging units, there may be a mixture within the delivery.



4. Affected parts

A list of the affected articles can be found in the attachment.

5. Data

Except for the packaging bag, all technical data and functional characteristics of the products remain unaffected by this measure. The data sheets of the affected articles will be completed with the ESD attribute under the point "Packing". The addition will be displayed on the data sheets from April 2023.

Packing	
Packaging	Tape
VPE length	332 mm
VPE width	332 mm
VPE height	38 mm
Tape depth (T2)	12.1 mm
Tape width (W)	32 mm
Tape pocket depth (K0)	11.6 mm
Tape pocket height (A0)	11.41 mm
Tape pocket width (B0)	19.2 mm
Tape pocket separation (P1)	16 mm
Tape hole separation (E)	1.75 mm
Tape pocket separation (F)	14.2 mm
Tape reel diameter Ø (A)	330 mm
Surface resistance	$R_s = 10^9 - 10^{12} \Omega$

We are very sorry for all the inconveniences caused and doing everything to adjust this product change as smooth as possible without big influence on delivery times and general functions.

For further questions please contact your sales office directly. All contacts for sales representatives are available here:

<http://www.weidmueller.com/contact>

Weidmüller will see this notification as accepted unless a separate procedure is requested in writing within 30 days of the issue date.

Best regards

Product Management

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 | 32758 Detmold | Germany

www.weidmueller.com